

## 4 IN 1 BULLET CAMERA PRO SERIES, 2 MP

CVBS HDCVI™

HDTVI AHD



### FEATURES

- Full HD resolution with Sony® CMOS sensor
- IR illumination up to 40 meters
- 2,8 ~ 12 mm varifocal lens
- Transmission distance up to 300 meters
- AWB, AGC, BLC, HLC, Digital WDR
- OSD menu
- 4 in 1 output (DIP switch): CVBS, HDCVI, HDTVI, AHD
- IP66
- 3 AXIS bracket with wiring holes

### ACCESSORIES



**HYU-251**  
Connection base

#### CAMERA

Image sensor	1/3 Sony® Exmor CMOS, 2 MP
Effective pixels	1920(H) x 1080(V)
Synchronization	Internal
Frames per second	PAL/NTSC: 25/30 fps @1080P
Electronic shutter	1/50s ~ 1/50.000s, 1/60s ~ 1/60.000s
IR illumination	5 led array: 40 meters
Minimum illumination	0,01 lux F1,2 (AGC On) / 0 lux IR ON
Video output	1 BNC AHD, HDCVI, HDTVI, CVBS (DIP switch)

#### LENS

Lens	2,8 ~ 12 mm
------	-------------

#### FUNCTIONS

Day/night	Auto (ICR)
OSD menu	Supported
White balance	AWB
Gain control	AGC
Backlight compensation	BLC, HLC, Digital WDR

#### ELECTRICAL & ENVIRONMENTAL

Power supply	12V DC (±10%) /700 mA
Consumption	8W
Working temperature	-10°C ~ +55°C
RH	<95% HR
Transmission distance	Up to 300 meters (theoretical) via 75-3 coaxial cable
Protection	IP66

#### PHYSICAL FEATURES

Case	Metal
Dimensions	285 x 105 x 105 mm