

4 IN 1 BULLET CAMERA PRO SERIES, 2 MP

CVBS HDCVI™

HDTVI AHD



FEATURES

- Full HD resolution with CMOS sensor Panasonic
- IR illumination up to 60 meters
- 2,8 ~ 12 mm autofocus motorized lens
- Transmission distance up to 300 meters
- AWB, AGC, BLC, HLC, real WDR 120dB, 2D/3D-DNR, defog
- Slow shutter, Smart IR, Sense Up
- Mirror, motion detection, privacy mask
- OSD menu
- 4 in 1 output (switch via button): CVBS output + triple output: CVI, TVI, AHD
- IP66
- 3 AXIS bracket with wiring holes

ACCESSORIES



HYU-252
Junction box

CAMERA

Image sensor	1/3 Panasonic CMOS, 2.1 MP
Effective pixels	1944(H) x 1092(V)
Frames per second	PAL/NTSC: 25/30 fps @1080P, 50/60 fps @720P
Electronic shutter	Auto, 1/25s ~ 1/50.000s
IR illumination	4 led array: 50 ~ 60 meters
Minimum illumination	0,02 lux F1,2 (AGC ON) / 0 lux IR ON
Video output	AHD, HDCVI, HDTVI, 1 BNC CVBS (button switch)

LENS

Lens	2,8 ~ 12 mm
Lens type	Motorized
Focus mode	Auto

FUNCTIONS

Day/night	Auto, Color, B/W, Ext
OSD menu	Supported
White balance	AWB, ATW, indoor, outdoor, manual
Gain control	AGC
Backlight compensation	BLC, HLC, real WDR 120dB
Noise reduction	2D/3D-DNR
Defog	Supported
Mirror	Supported
Motion detection	Supported
Privacy mask	Supported

ELECTRICAL & ENVIRONMENTAL

Power supply	12V DC (±10%) /670 mA
Consumption	<8W
Working temperature	-20°C ~ +60°C
RH	10% ~ 90% HR
Transmission distance	Up to 300 meters (theoretical) via 75-3 coaxial cable
Protection	IP66

PHYSICAL FEATURES

Case	PVC & metal
Dimensions	250 x 90 x 75 mm